


Squeeeeek No More[®] CONTRACTOR PACK

Stops floor squeaks quickly and easily from above the carpet

ELIMINATE PESKY FLOOR SQUEAKS

The tools and screws in the Squeeeeek No More kit allow you to safely fix squeaks through carpeted floors without having to pull it back and re-stretch it to its original position. The kit also includes a fixture that allows you to work on hardwood and linoleum floors resulting in a securely fastened board with a #8 screw that looks like a counter-sunk trim nail. The kit also includes a tool to quickly find the joist in carpeted floors.

The key to the system is the specially scored screw. It starts at the tip with 8 threads per inch. One inch up it switches to 9 threads per inch. This pitch change draws the board down as the screw descends into the flooring. The tooling stops the screw at the point where the score on the screw is safely below the wood. The head of the screw is then snapped off, leaving nothing to see or feel in carpet and a small hole to fill with wood putty in hardwood floors.



Contents:

- 1-Zinc Alignment & Depth Control Fixture
- 1- Hardwood Floor Fixture
- 2-Special Driver Bits
- 6-Joist Finders
- 500-Specially Scored Screws



Scan the QR code with your smartphone to view a video about the product or go to www.floorscrews.com

STEP 1



In the area of the squeak find the joist from above the floor using the Joist Finding Tool in the kit. Then push the Alignment and Depth Control Fixture firmly into the carpet.

STEP 2



Using the driver bit provided, drive the screw down as far as the fixture will allow.

STEP 3



Slip the Screw Gripper over the screw head and rock the fixture left to right, snapping the head off. The screw breaks at the score that is set slightly below the wood of the floor.

STEP 4



There is no damage to the carpet and nothing to feel with your bare foot.

O'Berry Enterprises, Inc.
800-459-8428 • 9-5 CST